

YOKOHAMA / MOTO POWER 4T

10W-30

TECHNICAL DATA SHEET | TDS

SEMI-SYNTHETIC FOUR-STROKE MOTORCYCLE ENGINE OIL

PRODUCT DESCRIPTION

YOKOHAMA MOTO POWER 4T 10W-30 is a semi-synthetic four-stroke motorcycle oil developed for engines that share lubrication with the transmission and wet clutch. Its balanced formulation supports engine cleanliness, wear control and stable clutch engagement during everyday riding.

APPLICATIONS

For air- or liquid-cooled four-stroke petrol motorcycles requiring SAE 10W-30, API SL and JASO MA2. Suitable for wet-clutch motorcycles with an integrated gearbox when these requirements are specified. Check separate gearbox or dry-clutch requirements independently. Select the appropriate oil type for JASO MB scooters and two-stroke engines.

PERFORMANCE SPECIFICATIONS

API SL

JASO MA2

TYPICAL TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	TYPICAL VALUE
SAE viscosity grade	SAE J300	10W-30
Kinematic viscosity at 40°C (mm ² /s)	ASTM D445	69.43
Kinematic viscosity at 100°C (mm ² /s)	ASTM D445	10.55
Viscosity index	—	144.80
Density at 15°C (kg/m ³)	ASTM D4052	863.3
Flash point, open cup (°C)	Open cup	230.7
Pour point (°C)	—	-36.0

Note: The values shown in this table are typical values and do not constitute product specifications. Minor variations may occur between production batches due to normal manufacturing tolerances.