

# YOKOHAMA / MOTO POWER 4T 15W-40

TECHNICAL DATA SHEET | TDS

FOUR-STROKE MOTORCYCLE ENGINE OIL

## PRODUCT DESCRIPTION

YOKOHAMA MOTO POWER 4T 15W-40 is designed for four-stroke motorcycle engines that use a shared oil circuit for the engine, gearbox and wet clutch. Its lubricating and friction characteristics support wear protection, engine cleanliness and reliable clutch engagement across everyday riding conditions.

## APPLICATIONS

For air- or liquid-cooled four-stroke petrol motorcycles specifying SAE 15W-40 and API SL, SJ or SH with JASO MA2 or MA. Suitable for shared-sump designs in which the engine, gearbox and wet clutch use the same oil. JASO MB scooters and two-stroke engines require oils intended for those applications.

## PERFORMANCE SPECIFICATIONS

API SL / SJ / SH

JASO MA2 / MA

## TYPICAL TECHNICAL CHARACTERISTICS

| PROPERTY                             | TEST METHOD | TYPICAL VALUE |
|--------------------------------------|-------------|---------------|
| SAE viscosity grade                  | —           | 15W-40        |
| Kinematic viscosity at 40°C (mm²/s)  | ASTM D445   | 104.33        |
| Kinematic viscosity at 100°C (mm²/s) | ASTM D445   | 14.15         |
| Viscosity index                      | ASTM D2270  | 137.00        |
| Density at 15°C (kg/m³)              | ASTM D4052  | 867.7         |
| Flash point, COC (°C)                | ASTM D92    | 230           |
| Pour point (°C)                      | —           | -31.5         |

Note: The values shown in this table are typical values and do not constitute product specifications. Minor variations may occur between production batches due to normal manufacturing tolerances.